



NHXH FE180/E30 0,6/1 kV, CHVE-V, CHFE-V 0,6/1 kV

0107), (DIN VDE  
 (DIN VDE 0108),  
 DIN VDE 0298 1 2 -

FE 180: 180 DIN VDE 0472 814 =  
 IEC 60331.  
 180  
 E 30: 30 (t=400C0),  
 ( 1 DIN VDE 0108 1).  
 DIN 4102 12.  
 30  
 30

DIN VDE 0295 1, 2 IEC 228 1 2

C

DIN VDE 0207, 5

0,6/1 V / 4 kV

+20 °C

DIN VDE 0295 1 IEC 228 1

DIN VDE ( )

10 x

-40 °C / +70 °C  
-5 °C / +50 °C

- DIN VDE 0482 266-2/HD 405.3, BS 4066  
3/ EN 50266-2/IEC 60332-3 ( DIN VDE 0472 804 C)  
- DIN VDE 0482 267/EN 50267-2-2/ IEC 60754-2 ( 813)  
DIN VDE 0472 815)  
- DIN VDE 0482 267/EN 50267-2-1/IEC 60754-1 ( 815)  
- DIN VDE 0482 268, HD 606, EN 50268-1+2/ IEC 61034-1+2, BS  
7622 1+2 ( DIN VDE 0472 816)  
- VDE 0472 814 = IEC 60331  
- DIN  
4102 12 (30 90 )

DIN VDE 0276

n x <sup>2</sup> / /

1 X 4re	8,0	38,0	105,0
1 X 6re	9,0	58,0	130,0
1 X 10re	10,0	96,0	170,0
1 X 16rm	11,0	154,0	250,0
1 X 25rm	12,0	240,0	370,0
1 X 35rm	13,0	336,0	460,0
1 X 50rm	15,0	480,0	600,0
1 X 70rm	17,0	672,0	840,0
1 X 95rm	19,0	912,0	1.100,0
1 X 120rm	21,0	1.152,0	1.380,0
1 X 150rm	23,0	1.440,0	1.670,0
1 X 185rm	26,0	1.776,0	2.080,0
1 X 240rm	28,0	2.304,0	2.690,0
1 X 300rm	30,0	2.880,0	3.250,0
2 X 1,5re	12,0	29,0	190,0
2 X 2,5re	13,0	48,0	220,0
2 X 4re	14,0	77,0	280,0
2 X 6re	15,0	115,0	340,0
2 X 10re	16,0	192,0	450,0
2 X 16rm	19,0	307,0	650,0
2 X 25rm	22,0	480,0	940,0

n x <sup>2</sup> / /

3 X 1,5re	12,0	43,0	220,0
3 X 2,5re	13,0	72,0	260,0
3 X 4re	14,0	115,0	340,0
3 X 6re	15,0	173,0	420,0
3 X 10re	17,0	288,0	570,0
3 X 16rm	20,0	461,0	800,0
3 X 25rm	23,0	720,0	1.180,0
3 X 35rm	26,0	1.080,0	1.520,0
3 X 50rm	29,0	1.440,0	2.000,0
3 X 70rm	35,0	2.016,0	2.860,0
3 X 95rm	39,0	2.736,0	3.770,0
3 X 120rm	43,0	3.456,0	4.680,0
3 X 150rm	48,0	4.320,0	5.740,0
3 X 185rm	53,0	5.328,0	7.150,0
3 X 240rm	59,0	6.912,0	9.230,0
3 X 25/16rm	24,9	1.430,0	873,0
3 X 35/16rm	27,2	1.789,0	1.162,0
3 X 50/25rm	31,0	2.402,0	1.680,0
3 X 70/35rm	35,1	3.258,0	2.352,0
3 X 95/50rm	40,6	4.455,0	3.216,0
3 X 120/70rm	44,4	5.538,0	4.128,0
4 X 1,5re	13,0	58,0	250,0
4 X 2,5re	14,0	96,0	310,0
4 X 4re	15,0	154,0	400,0
4 X 6re	17,0	230,0	500,0
4 X 10re	19,0	384,0	700,0