



NHXH FE180/E90 0,6/1 kV, CHVE-V, CHFE-V 0,6/1 kV

0107), (DIN VDE
 (DIN VDE 0108),
 DIN VDE 0298 1 2 -

FE 180: 180 DIN VDE 0472 814 =
 IEC 60331.
 180
 E 90: 90 (t=400C0),
 (1 DIN VDE 0108 1).
 DIN 4102 12.
 90
 90

DIN VDE 0295 1, 2 IEC 228 1 2
 C / /

- - DIN VDE 0207, 5

0,6/1 V / 4 kV

+20 °C
 DIN VDE 0295 1 IEC 228 1

DIN VDE ()

10 x

-40 °C / +70 °C
 - 5 °C / +50 °C

- DIN VDE 0482 266-2/HD 405.3, BS 4066
 3/ EN 50266-2/IEC 60332-3 (DIN VDE 0472 804 C)
 - DIN VDE 0482 267/EN 50267-2-2/ IEC 60754-2 (
 DIN VDE 0472 813)
 - DIN VDE 0482 267/EN 50267-2-1/IEC 60754-1 (
 DIN VDE 0472 815)
 - DIN VDE 0482 268, HD 606, EN 50268-1+2/ IEC 61034-1+2, BS
 7622 1+2 (DIN VDE 0472 816)
 - VDE 0472 814 = IEC 60331
 - DIN
 4102 12 (30 90)

DIN VDE 0276

n x ² / /

1 X 16rm	12,0	154,0	287,0
1 X 25rm	13,0	240,0	397,0
1 X 35rm	15,0	336,0	520,0
1 X 50rm	16,0	480,0	672,0
1 X 70rm	17,0	672,0	913,0
1 X 95rm	19,0	912,0	1.122,0
1 X 120rm	21,0	1.152,0	1.353,0
1 X 150rm	23,0	1.440,0	1.686,0
1 X 185rm	25,0	1.776,0	2.073,0
1 X 240rm	29,0	2.304,0	2.880,0
1 X 300rm	31,0	2.880,0	3.444,0
1 X 400rm	34,0	3.840,0	4.316,0
2 X 1,5re	13,0	29,0	245,0
2 X 2,5re	14,0	48,0	289,0
2 X 4re	15,0	77,0	367,0
2 X 6re	16,0	115,0	440,0
2 X 10re	18,0	192,0	574,0
2 X 16rm	21,0	307,0	851,0
2 X 25rm	24,0	480,0	1.168,0
2 X 35rm	27,0	672,0	1.491,0
2 X 50rm	30,0	960,0	1.938,0
2 X 70rm	34,0	1.344,0	2.609,0
2 X 95rm	39,0	1.824,0	3.421,0
2 X 120rm	41,0	2.304,0	4.040,0

n x ² / /

3 X 1,5re	14,0	43,0	274,0
3 X 2,5re	15,0	72,0	347,0
3 X 4re	16,0	115,0	423,0
3 X 6re	17,0	173,0	515,0
3 X 10re	18,0	288,0	686,0
3 X 16rm	23,0	461,0	1.021,0
3 X 25rm	26,0	720,0	1.452,0
3 X 35rm	29,0	1.008,0	1.831,0
3 X 50rm	33,0	1.440,0	2.418,0
3 X 70rm	37,0	2.016,0	3.282,0
3 X 95rm	42,0	2.736,0	4.319,0
3 X 120rm	44,0	3.456,0	5.144,0
3 X 150rm	49,0	4.320,0	6.353,0
3 X 185rm	54,0	5.328,0	7.763,0
3 X 240rm	61,0	6.912,0	10.083,0
3 X 35/16rm	30,0	1.162,0	2.025,0
3 X 50/25rm	34,0	1.680,0	2.726,0
3 X 70/35rm	39,0	2.352,0	3.676,0
3 X 95/50rm	44,0	3.216,0	4.831,0
3 X 120/70rm	47,0	4.128,0	5.903,0
3 X 150/70rm	51,0	4.992,0	7.064,0
3 X 185/95rm	57,0	6.240,0	8.759,0
3 X 240/120rm	63,0	8.064,0	11.299,0

n x ² / /

3 X 35/16rm	30,0	1.162,0	2.025,0
3 X 50/25rm	34,0	1.680,0	2.726,0
3 X 70/35rm	39,0	2.352,0	3.676,0
3 X 95/50rm	44,0	3.216,0	4.831,0
3 X 120/70rm	47,0	4.128,0	5.903,0
3 X 150/70rm	51,0	4.992,0	7.064,0
3 X 185/95rm	57,0	6.240,0	8.759,0
3 X 240/120rm	63,0	8.064,0	11.299,0
4 X 1,5re	15,0	58,0	342,0
4 X 2,5re	16,0	96,0	414,0
4 X 4re	17,0	154,0	510,0
4 X 6re	19,0	230,0	626,0
4 X 10re	21,0	384,0	866,0
4 X 16rm	25,0	614,0	1.261,0
4 X 25rm	29,0	960,0	1.801,0
4 X 35rm	32,0	1.344,0	2.327,0
4 X 50rm	36,0	1.920,0	3.049,0
4 X 70rm	41,0	2.688,0	4.139,0
4 X 95rm	46,0	3.648,0	5.458,0
4 X 120rm	49,0	4.608,0	6.527,0
4 X 150rm	54,0	5.760,0	8.094,0
4 X 185rm	60,0	7.104,0	9.910,0
4 X 240rm	67,0	9.216,0	12.870,0
5 X 1,5re	16,0	72,0	399,0
5 X 2,5re	18,0	120,0	485,0
5 X 4re	19,0	192,0	600,0
5 X 6re	21,0	288,0	770,0
5 X 10re	23,0	480,0	1.037,0
5 X 16rm	28,0	768,0	1.548,0
5 X 25rm	32,0	1.200,0	2.207,0
5 X 35rm	35,0	1.680,0	2.825,0
5 X 50rm	40,0	2.500,0	3.722,0
5 X 70rm	45,0	3.360,0	5.063,0