



NYCWY 0,6/1 kV, CYKYDY SE, CYKFY SE 0,6/1 kV

-
-
-
-
-
-
-

0,6/1 kV
4 kV

CW

()

DIN VDE 0295 1, 2 IEC 228 1 2

DIN VDE 0207, 5

0,6/1 V / 4 kV

DIN VDE 0295 1 IEC 228 1
+20 °C

DIN VDE ()

4 x
12 x

-40 °C / +70 °C
- 5 °C / +50 °C

B DIN VDE 0472, 804 IEC 332-1

DIN VDE 0271 IEC 502

n x ²

/

/

2	X	10re/10	19,0	312,0	600,0
2	X	16re/16	21,0	489,0	830,0
3	X	10re/10	20,0	408,0	720,0
3	X	16re/16	22,0	643,0	990,0
3	X	25rm/25	26,0	1.003,0	1.480,0
3	X	25rm/16	26,0	902,0	1.400,0
3	X	35rm/35	28,0	1.402,0	1.950,0
3	X	35rm/16	28,0	1.190,0	1.750,0
3	X	35sm/35	27,0	1.402,0	1.800,0
3	X	35sm/16	27,0	1.190,0	1.600,0
3	X	50sm/50	29,0	2.000,0	2.350,0
3	X	50sm/25	29,0	1.723,0	2.110,0
3	X	70sm/70	34,0	2.796,0	3.220,0
3	X	70sm/35	33,0	2.410,0	2.910,0
3	X	95sm/95	38,0	3.791,0	4.380,0
3	X	95sm/50	38,0	3.296,0	3.920,0
3	X	120sm/120	42,0	4.786,0	5.370,0
3	X	120sm/70	41,0	4.236,0	4.880,0
3	X	150sm/150	46,0	5.970,0	6.590,0
3	X	150sm/70	45,0	5.100,0	5.820,0
3	X	185sm/95	50,0	6.383,0	7.370,0
3	X	240sm/120	57,0	8.242,0	9.400,0

n x ² / /

4 X 10re/10	21,0	504,0	850,0
4 X 16re/16	24,0	796,0	1.210,0
4 X 25rm/16	28,0	1.142,0	1.720,0
4 X 35sm/16	29,0	1.526,0	1.970,0
4 X 50sm/25	33,0	2.203,0	2.680,0
4 X 70sm/35	37,0	3.082,0	3.710,0
4 X 95sm/50	43,0	4.208,0	5.020,0
4 X 120sm/70	47,0	5.388,0	6.200,0
4 X 150sm/70	51,0	6.540,0	7.500,0